MODE 2 PORTABLE AC CHARGING KIT

AC PORTABLE CHARGER

22 kW · 3-phase

A Mode 2 portable charger that turns any 32 A CEE socket into a 22 kW charging point — no wall box, no installation. The control unit, 5 m Type 2 cable and Schuko adapter travel together in one rugged kit.



22 kW	Mode 2	IP66	5 m
Max. power (3-ph, 32 A)	IC-CPD	IK10 enclosure	Type 2 cable

KEY FEATURES

No installation
Plug into a correctly installed 32 A CEE socket and charge.

One-touch power selection
16 A / 32 A (11 kW / 22 kW).

Residual-current protection
30 mA AC + 6 mA DC with automatic recovery.

Temperature monitoring
Supply plug and internal temperature are monitored continuously.

Schuko adapter
CEE-to-Schuko adapter included for 3.7 kW household charging.

APPLICATIONS

- Homes without a wall box
- Workshops and dealerships
- Fleet depots
- Temporary sites and events

TECHNICAL SPECIFICATIONS

Maximum Power	22 kW (3-phase, 32 A) · 11 kW (16 A)
Supply	3 × 230/400 V AC, 3P + N + PE, 50/60 Hz
Charging Mode	Mode 2 (IC-CPD)
Residual Current	30 mA AC + 6 mA DC
Vehicle Connector	Type 2 (IEC 62196-2), 5 m cable
Supply Plug	CEE 32 A 5-pin + CEE–Schuko 16 A adapter
Enclosure	PC + ABS, IP66 / IK10
Dimensions · Weight	280 × 110 × 63 mm (control unit) · 4.6 kg
Standards	IEC 61851-1, IEC 62752, IEC 62196-2, IEC 61851-21-2, CE

Specifications are subject to change without notice. © 2026 Predixon OÜ, Tallinn, Estonia.

info@predixon.net · +90 850 242 55 72
Predixon OÜ · Tallinn, Estonia