PREDIXON
PRO-CHARGE

WALL OR PEDESTAL-MOUNTED DC CHARGING

DC WALL BOX

30 kW DC

The same 30 kW DC platform as Mobile SC, fixed to a wall or pedestal for permanent installations — the stationary option where units don't need to move. Ideal where a site wants DC speed without the footprint of a floor-standing fast charger.



30 kW	150–1000 V DC	CCS2	IP65
DC output power	Voltage range	Tethered cable, 5 m	IK10 enclosure

KEY FEATURES

Flexible mounting
Wall-mount or pedestal-mount from the same unit.

Tethered cable
Tethered CCS2 cable with holster.

User interface
Colour display, RFID card reader and emergency stop.

Shared platform
Spare parts and service know-how shared with Mobile SC.

Cloud management
OCPP 1.6J; works with any OCPP backend, including Strova by Predixon.

Built for harsh sites
IP65 / IK10 enclosure; operation up to +65 °C, derating above +55 °C.

APPLICATIONS

- Fixed depot bays
- Facility car parks
- Dealerships and service

TECHNICAL SPECIFICATIONS

DC Output	30 kW
DC Voltage Range	150–1000 V DC
Connector	CCS Combo 2, tethered, 5 m
AC Input	400 V AC, 3P + N + PE, 50/60 Hz
User Interface	Colour display · RFID reader · emergency stop
Connectivity · Protocol	Wi-Fi · Ethernet · 4G-LTE · OCPP 1.6J
Dimensions (W × H × D)	620 × 570 × 240 mm
Mounting	Wall or pedestal
Environment	IP65 / IK10
Operating temperature	Up to +65 °C; automatic derating above +55 °C

Specifications are subject to change without notice. © 2026 Predixon OÜ, Tallinn, Estonia.

predixon.net

omerderya.dinc@predixon.net · +90 850 242 55 72
Predixon OÜ · Tallinn, Estonia